

İSOS ENERJİ

25/50/100//150/205/340/410/M



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*



PEAK POWER	OPEN CIRCUIT VOLTAGE Voc(V)	SHORT CIRCUIT CURRENT Isc(A)	PEAK VOLTAGE Vmp(V)	PEAK CURRENT IMP (A)	SIZE (mm)	CELL NUMBER (pcs)	NET WEIGHT (kg)
25M	23,80	1,49	20,70	1,39	430*360*25	36	1,7
50M	23,80	2,54	20,70	2,5	430*670*25	36	3,8
100M	23,80	5,07	20,70	5,05	800*670*25	36	7,0
150M	23,80	7,61	20,70	7,36	1150*670*30	36	9,0
205M	23,80	9,99	20,70	9,79	1480*670*30	36	10,9
340M	34,50	10,53	39,68	9,57	990*1640*35	60	19,0
410M	23,80	9,99	20,70	9,66	990*1960*40	72	23,0

İSOS ENERJİ MÜH.LTD.ŞTİ

Halkapınar Mah. 1376 Sokak Boran Plaza No:3/D

Konak/İZMİR

0232 433 09 35

Info@isosenerji.com