

İSOS ENERJİ

10/22/42/60/85/105/125/170/280/335P



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*



PEAK POWER	OPEN CIRCUIT VOLTAGE Voc(V)	SHORT CIRCUIT CURRENT Isc(A)	PEAK VOLTAGE Vmp(V)	PEAK CURRENT IMP (A)	SIZE (mm)	CELL NUMBER (pcs)	NET WEIGHT (kg)
10P	22,10	0,67	18,00	0,56	30*30*25	36	1,3
22P	22,10	1,38	18,00	1,22	430*36*25	36	1,68
42P	22,10	2,58	18,00	2,33	430*670*25	36	3,8
60P	22,10	3,68	18,00	3,33	600*670*25	36	5,2
85P	22,10	4,96	18,00	4,72	800*670*25	36	7,0
105P	22,10	6,10	18,00	5,83	970*670*35	36	8,5
125P	22,10	7,30	18,00	6,94	1150*670*30	36	9,5
170P	22,30	9,50	18,60	9,14	1480*670*30	36	11,9
285P	37,80	9,53	31,30	9,10	990*1960*40	60	23,0
335P	44,20	9,05	38,50	8,70	992*1956*40	72	23,0

İSOS ENERJİ MÜH.LTD.ŞTİ

Halkapınar Mah. 1376 Sokak Boran Plaza No:3/D

Konak/İZMİR

0232 433 09 35

info@isosenerji.com